



05000A Motor Oil 10W-40 Premium Synthetic Diesel

Document versie: 30 april 2014



Art. nr.	Volume	Items per unit	Items per pallet
05001A	1 L	6	450
05005A	5 L	4	112
05020A	20 L	1	30
05060A	60 L	1	12
05205A	205 L	1	2
05999A	1000 L	1	0
P05000A	bulk	1	0

Beschrijving

Premium synthetische motorolie voor motoren van bedrijfswagens.

Specificaties

ACEA E4-08/E7-08
 API CI-4
 Cummins CES 20077 / 20078
 Deutz DQC III-10
 Mack EO-M Plus
 MAN M3277
 MB-Approval 228.5
 MTU TYPE-3
 Renault RLD-2 / RXD
 Scania LDF-2
 Volvo VDS-3

Standaardanalyses

Dichtheid bij 15°C	0,872	kg/l
Kinematische viscositeit bij 40°C	101.0	mm ² /s
Kinematische viscositeit bij 100°C	13.5	mm ² /s

Pagina 1/2



Viscositeitsindex	133	
Dynamische viscositeit bij -25°C	6100	mPa·s
Vlampunt COC	220	°C
Stolpunt	-36	°C
Total Base nummer	12.2	mgKOH/g
Sulfaatas	1.4	mass%
Noack verdampingverlies	12.5	mass%